PONSSE firefighting equipment for forwarders



PONSEE is introducing firefighting equipment to be installed in the load spaces of forwarders for extinguishing wildfires.

Forest machine is the most natural and effective way to access a forest fire area. Operations in difficult terrain come as second nature to them, and they have more than enough capacity in their hydraulic system for demanding conditions. The firefighting equipment is delivered to the fire location as a single package – and after it has been connected to forest machine hydraulics, the equipment is ready to operate.

The 10 m³ water tank of the firefighting equipment can be filled with its own pump from a natural water source or the tank of a fire truck. The water cannon has a range of 47 metres and a turning radius of 360 degrees. It takes 5 to 10 minutes to refill the tank. The filling hose is guided by the forwarder's boom and the strainer on the tank roof takes out the biggest debris. The water cannon is controlled with the remote control. The system draws its power from the hydraulics of the forwarder.

1

MORE DETAILS CHALLENGE ADDRESSED **DOMAIN** TYPE OF SOLUTION 1.- Improve forest resilience and adaption to climate Forest disturbances, risks Smart machinery, equipment change **KEYWORDS DIGITAL SOLUTION** INNOVATION forest machine No Yes forwarder firefighting **COUNTRY OF ORIGIN** SCALE OF APPLICATION START AND END YEAR Finland Cross-border/multi-lateral (several countries) CONTACT DATA OWNER OR AUTHOR **REPORTER Ponsse** Juha Harverinen juha.haverinen@ponsse.com **REFERENCES** AND RESOURCES _____ MAIN WEBSITE **RESOURCES** https://www.ponsse.com/en/web/guest/products/tailored-solutions/product/-/p/firefightingequipment **PROJECT WEBSITE** PROJECT REFERENCE



PROJECT UNDER WHICH THIS FACTSHEET HAS BEEN CREATED

Rosewood 4.0

POST DATE

9 Dec 2021







This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No. 862681

A TOOL FROM ROSEWOOD 4.0, DESIGNED AND DEVELOPED BY





1