Joint wood terminals



A joint wood terminal means a built-up area suitable for the storage and handling of timber species. The operations performed at the wood terminal are determined by the operator according to their needs.

One of the challenges in wood mobilization is small-scale wood units within long distances from the nearest roads. These units are not profitable for harvesting, since forest and long-distance transportation are of high costs. The answer to the challenge might lie in bigger wood terminals where wood from multiple small-scale units would be gathered from the same area for intermediate storage. In general, storing the wood is sensible at a distance of about 100 to 150 km from the site of use. The best location for intermediate storage is at the beginning of forest roads.

In Lapland, for instance, a few big terminals have been built close to the railway to advance the efficiency of wood transportation by train. In the provinces, larger terminals are usually located mainly according to the needs of industry and large forestry companies. Benefits of common terminals occur especially in wintertime, when maintenance of storage area could be done commonly or by the certain terminal operator. The joint terminals are well suited for energy wood and wood for which the need for storage is at a different time. This allows continuous use of area.

Operating culture, various practices, and lack of cooperation of the actors are experienced to restrict the wider deployment of common terminals. However, an increase in wood flows will require building more terminals. There is a need for more joint terminals, but it requires cooperation between forest service providers. It would be highly useful to gather the intermediate storage places in one map-based spatial database, which would be open-accessed for all the service providers. This would advance bringing together different actors in the wood procurement chain. In summary, the main benefits comprise:

- · Joint wood terminals of forest companies for short-term storage of wood
- Profitable harvesting from the small-scale unit
- Efficiency in wood transportation by train
- Less environmental effects because of centralized terminals

1

PODROBNOSTI

PÔVOD DREVA MOBILZAČNÝ POTENCIÁL

Les High

DRUH DREVA

Kmeňové drevo POTENCIÁL UDRŽATEľNOSTI - HODNOTA

--

UVAŽOVANÝ DRUH DREVA UľAHČENIE IMPLMENTÁCIE

Stemwood, energy wood Medium

VPLYV NA ŽIVOTNÉ PROSTREDIE A BIODIVERZITU UľAHČENIE IMPLMENTÁCIE - HODNOTENIE

Environmental effects burdening only big terminals instead of several small

terminals.

DOPAD NA PRÍJMY KľúČOVÉ PREPOKLADY

Positive Involve all relevant stakeholders in the development.

POTENCIÁL VYUŽITIA TYP PODUJATIA, NA KTOROM BOL TENTO BPI PREZENTOVANÝ

--

ROZBOČOVAČ DOPAD NA ZAMESTNANOSť

Severný uzol Positive

EKONOMICKÝ VPLYV NáKLADY NA IMPLEMENTÁCIU (EURO - €)

Cost-effectiveness in joint maintenance of terminal and in transportation. --

POTREBA ŠPECIFICKÝCH ZNALOSTÍ

--

VIAC INFORMáCIí

RIEŠENá VýZVA **DOMAIN TYP RIEŠENIA** 5. Zlepšenie hospodárskej a environmentálnej Ťažba, infraštruktúra, logistika Platformy pre spoluprácu, logistické uzly výkonnosti dodávateľských reťazcov v lesníctve KľúčOVé SLOVá **DIGITALNE RIEŠENIE** INOVáCIE terminal Nie Nie transportation KRAJINA PôVODU ROZSAH APLIKáCIE **ZAČIATOK A KONIEC ROKA** Fńsko Národný

PROJEKT, V RáMCI KTORÉHO BOL TENTO INFORMAČNÝ PREHľAD VYTVORENÝ

Rosewood

DáTUM ODOSLANIA

17 sep 2019







This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No. 862681

A TOOL FROM ROSEWOOD 4.0, DESIGNED AND DEVELOPED BY



