PONSSE firefighting equipment for forwarders



PONSEE is introducing firefighting equipment to be installed in the load spaces of forwarders for extinguishing wildfires.

Forest machine is the most natural and effective way to access a forest fire area. Operations in difficult terrain come as second nature to them, and they have more than enough capacity in their hydraulic system for demanding conditions. The firefighting equipment is delivered to the fire location as a single package – and after it has been connected to forest machine hydraulics, the equipment is ready to operate.

The 10 m³ water tank of the firefighting equipment can be filled with its own pump from a natural water source or the tank of a fire truck. The water cannon has a range of 47 metres and a turning radius of 360 degrees. It takes 5 to 10 minutes to refill the tank. The filling hose is guided by the forwarder's boom and the strainer on the tank roof takes out the biggest debris. The water cannon is controlled with the remote control. The system draws its power from the hydraulics of the forwarder.

1

VEč **PODROBNOSTI** IZZIV DOMENA TIP REŠITVE 1. Izboljšava odpornosti gozdov in prilagoditev na Motnje, tveganja, odziv na naravne nesreče Pametni stroji, oprema klimatske spremembe KLJUČNE BESEDE **DIGITALNE REŠITVE** INOVACIJA forest machine No Da forwarder firefighting IZVORNA DRŽAVA **OBSEG UPORABE** ZAČETNO IN KONČNO LETO Čezmejni / Transnacionalni Finska **KONTAKTN PODATKI** LASTNIK OZ. AVTOR **POROČEVALEC** Ponsse Juha Harverinen juha.haverinen@ponsse.com **REFERENCES** AND RESOURCES. **SPLETNA STRAN** VIRI https://www.ponsse.com/en/web/guest/products/tailored-solutions/product/-/p/firefightingequipment SPLETNA STRAN PROJEKTA REFERENCA PROJEKTA



PROJEKT, V OKVIRU KATEREGA SO BILI ZBRANI OSNOVNI PODATKI

Rosewood 4.0

DATUM OBJAVE

9 Dec 2021







This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No. 862681

A TOOL FROM ROSEWOOD 4.0, DESIGNED AND DEVELOPED BY





1