Joint wood terminals



A joint wood terminal means a built-up area suitable for the storage and handling of timber species. The operations performed at the wood terminal are determined by the operator according to their needs.

One of the challenges in wood mobilization is small-scale wood units within long distances from the nearest roads. These units are not profitable for harvesting, since forest and long-distance transportation are of high costs. The answer to the challenge might lie in bigger wood terminals where wood from multiple small-scale units would be gathered from the same area for intermediate storage. In general, storing the wood is sensible at a distance of about 100 to 150 km from the site of use. The best location for intermediate storage is at the beginning of forest roads.

In Lapland, for instance, a few big terminals have been built close to the railway to advance the efficiency of wood transportation by train. In the provinces, larger terminals are usually located mainly according to the needs of industry and large forestry companies. Benefits of common terminals occur especially in wintertime, when maintenance of storage area could be done commonly or by the certain terminal operator. The joint terminals are well suited for energy wood and wood for which the need for storage is at a different time. This allows continuous use of area.

Operating culture, various practices, and lack of cooperation of the actors are experienced to restrict the wider deployment of common terminals. However, an increase in wood flows will require building more terminals. There is a need for more joint terminals, but it requires cooperation between forest service providers. It would be highly useful to gather the intermediate storage places in one map-based spatial database, which would be open-accessed for all the service providers. This would advance bringing together different actors in the wood procurement chain. In summary, the main benefits comprise:

- Joint wood terminals of forest companies for short-term storage of wood
- Profitable harvesting from the small-scale unit
- Efficiency in wood transportation by train
- Less environmental effects because of centralized terminals

PODROBNOSTI IZVOR LESA POTENCIAL ZA MOBILIZACIJO Gozd High TIP LESA Okrogli les TRAJNOST - VREDNOST VRSTA OBRAVNAVANEGA LESA **ENOSTAVNOST IZVEDBE** Stemwood, energy wood Medium VPLIV NA OKOLJE IN BIODIVERZITETO **ENOSTAVNOST IZVEDBE - OCENJEVANJE** Environmental effects burdening only big terminals instead of several small terminals. **VPLIV NA PRIHODKE** KLJUČNI PREDPOGOJI Involve all relevant stakeholders in the development. Positive POTENCIAL IZKORIŠČANJA VRSTA DOGODKA, NA KATEREM JE BIL PREDSTAVLJEN TA BPI **VOZLI**ŠČ**E** VPLIV NA DELOVNA MESTA Severno vozlišče Positive **GOSPODARSKI VPLIV** STROŠKI IZVEDBE (EURO - €) Cost-effectiveness in joint maintenance of terminal and in transportation.

POTREBNO SPECIFIČNO ZNANJE

__

IZZIV	DOMENA	TIP REŠITVE
5. Izboljšanje gospodarske in ekološke učinkovitosti	Sečnja in spravilo, infrastruktura, logistika	Platorma za sodelovanje, logistični centri
gozdne oskrbovalne verige		
KLJUČNE BESEDE	DIGITALNE REŠITVE	INOVACIJA
terminal	No	Ne
transportation		
IZVORNA DRŽAVA	OBSEG UPORABE	ZAČETNO IN KONČNO LETO
Finska	Nacionalni	

PROJEKT, V OKVIRU KATEREGA SO BILI ZBRANI OSNOVNI PODATKI

Rosewood

DATUM OBJAVE

17 Sep 2019







This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No. 862681

A TOOL FROM ROSEWOOD 4.0, DESIGNED AND DEVELOPED BY





