Development of visual and mechanical sorting tools for the enhancement of structural sawn timber



Structural sawn timber intended for construction must offer similar guarantees to those offered by other materials and products intended for the structural construction sector. For this purpose, it is necessary to develop classification tools that allow manufacturers and marketers to certify the strength and stiffness values of all the wood that is placed on the market (adjusted to the species and origin that corresponds).

It is, in addition to being a legal obligation, a tool for the valuation of wood that is enabling a competitive improvement of its industrial network.

Technological development of structural sawn timber not only enables it to be directly promoted in the construction sector as a construction element, but also to be incorporated into the manufacture of technological products with high added value, such as glued laminated timber, duos, trios, CLT, prefabricated panels... These are high value-added products that require high levels of competitiveness that cannot be achieved without their main raw material, structural sawn timber, increasing its competitiveness, optimising its manufacturing times and its declared mechanical properties

Visual classification tools have been developed for the main commercial wood species found in Spanish forest stands, such as Pinus sylvestris, Pinus insigne, Pinus nigra, Pinus pinaster, Abies alba, Pseudotsuga menziesii, Quercus rubra, Castanea sativa and Eucalyptus globulus. Tools that in many cases enable the possibility of classifying structural sawn timber into three structural qualities, which allows the different qualities of wood that the timber industry places on the construction market to be classified and valued.

Mechanical classification systems are currently being developed for the main species of the Pinus genus. This is one more step in the competitive improvement of this type of wood, as it improves the classification times and the classifying performance in the different mechanical qualities.

1

Both developments have enhanced the value of the wood of the different wood species characterized, and have promoted its use in construction.

DETALJER	
VEDENS URSPRUNG Industri TRäTYP Rundvirke	MOBILISERINGSPOTENTIAL 300,000 m3 HåLLBARHETS POTENTIAL - VÄRDE
TYP AV TRä Pinus sylvestris, Pinus nigra, Pinus radiata, Pinus pinaster, Pseudotsuga menziessii, Larix sp, Quercus rubra, Abies alba	ENKEL IMPLEMENTERING Very easy
PåVERKAN På MILJö & BIOLOGISK MåNGFALD Positive, it mobilizes wood with a proper forest management	ENKEL IMPLEMENTERING - UTVäRDERING
EKONOMISK EFFEKT Positive, more quality timber is mobilized KOMMERSIELL POTENTIAL	NYCKEL FÖRUTSÄTTNINGAR Experience on manufacturing and classification of structural timber TYP AV EVENEMANG DÄR DENNA BPI HAR PRESENTERATS
NAV 	EFFEKT ANTAL ANSTÄLLDA Positive through better competitiveness
EKONOMISK PåVERKAN Structural timber value increases in 10€/m3 approximately	KOSTNADER FÖR IMPLEMENTERING (EURO - €)

SPECIFIKA KUNSKAPSBEHOV

Knowledge about Phisical-mechanical properties of wood. Harmonized rules

needed

MER INFORMATION			
UTMANING SOM ADRESSERAS	DOMäN	TYPE AV LÖSNING	
	Skogindustri, bio/cirkulär ekonomi		
	Industri for träbyggnation		
NYCKELORD	DIGITAL LÖSNING	INNOVASION	
	Nej	Nej	
UPPHOVSLAND	POTENTIAL	START OCH SLUTÅR	
Spanien	Nationell	2011 -	
KONTAKT			
INFORMASION			
ÄGARE ELLER FÖRFATTARE	RAPPORTÖR		
edgar.lafuente@cesefor.com			
REFERENCES			
AND RESOURCES			
LIEMOIDA (LILIVIJDOIDA)	PEGURAER		
HEMSIDA (HUVUDSIDA)	RESURSER		
http://www.cesefor.com			
PROJEKTETS HEMSIDA			
PROJEKTREFERENS			

PROJEKT SOM DETTA FACTSHEET SKAPATS INOM

Rosewood

DATUM FÖR INLÄGG

30 aug 2019







This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No. 862681

A TOOL FROM ROSEWOOD 4.0, DESIGNED AND DEVELOPED BY



